

ShowerTablet Select

Bath thermostat 400 for exposed installation

Finish: **Brushed Bronze** Art. no. : **24340140**



Description

product features


- rotatable bath spout
- designed to run 2 outlets
- simultaneous utilisation by 2 outlets
- temperature and volume control
- Select push button on / off control for 2 outlets
- CoolContact thermostat: Prevents the housing from heating up, making showering even safer
- Maximum flow rate (at 3 bar): 18.7 l/min
- Flow rate for bath spout (at 3 bar): 18.7 l/min
- Flow rate of hand shower (at 3 bar): 15.9 l/min
- Min. operating pressure: 1 bar
- Max. operating pressure: 10 bar
- Safety stop at 40°C
- Maximum temperature can be adjusted on installation
- with isolated water conduction
- Non-return valve
- protected against backflow, according to DIN EN 1717
- with silencer
- Material handles: plastic
- shelf made of plastic
- Shelf colour: graphite
- Centre distance: 150 mm ± 12 mm
- dirt filter included
- thermostat is delivered with buttons hand shower and bath tub
- if running with a pump, please specify a universal (negative head) pump
- WRAS 2310357

Article Details

Price excl. VAT

£ 650.00

Technology



Design awards



reddot winner 2021



Certificates / Sustainability



ShowerTablet Select
Bath thermostat 400 for exposed installation
 Finish: **Brushed Bronze** Art. no. : **24340140**



Product image



Scale drawing

