# Mira Excel

Mixer Shower Range

SUITABLE FOR ALL SYSTEMS 5 YEAR WARRANTY

Unbeatable on all pressures, the Mira Excel is the UK's number one mixer shower.

### **Product Information**

Description	Colour	Product No.
Mira Excel EV	Chrome	1.1518.300
Mira Excel BIV	Chrome	1.1518.303
Mira Excel BIR	Chrome	1.1518.307
Mira Excel Exposed Valve Only	Chrome	1.1518.309
Mira Excel Built-in Valve Only	Chrome	1.1518.311

### Features & Benefits

#### Temperature control

Thermostatic temperature stability

#### Easy to fit

Quickly and easily fits onto reversed inlet supplies

EV has adjustable inlets (150-155mm)

#### Easy to service

Large, long-life filters and replaceable cartridge

#### For your customer

Separate flow and temperature controls

Maximum temperature stop – enhances safety (comfort override)

Ceramic flow control resists limescale

Mira Magni-flo $^{\rm TM}$  technology delivers up to 3x more flow, even at low pressure

Unrivalled performance on any pressure

 $4\ \rm spray\ 9cm\ showerhead\ with\ rub-clean\ nozzles\ (except\ BIR\ which\ has\ one\ single\ spray)$ 





## **Product Specification**

#### **Tech Details**

Control type: Thermostatic

Water entry points: Rising, falling or rear

Inlet connections: 15 mm compression (EV, BIV & BIR)

Outlet connections: 1/2" BSP Male Flat Face (EV) or 15mm compression (BIV & BIR)

Reversed inlets supported: Yes

### Supply Conditions (hot and cold)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating); 55°C-65°C (recommended)

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Flow rate (at handset): 13 l/min at 0.5 bar

Temperature stability:  $\pm 1$ °C


Automatic shutdown: Shutdown within 2 secs


Factory set to safe max temp: Factory set to 41°C (maximum 46°C)

Adjustable maximum temperature for on-site conditions

### **Dimensions**







Built-in Valve

