

# Mira Evoco Dual Bathfill

## Mixer Shower



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Beauty. Built-in. With illuminating Mira HydroGlo™ technology fully concealed mixer shower and bath filler. In three stunning finishes.

### Product Information

Description	Colour	Product No.
Mira Evoco Bath Fill and Shower with HydroGlo™ Technology	Chrome	1.1967.006
Mira Evoco Bath Fill and Shower with HydroGlo™ Technology	Matt Black	1.1967.007
Mira Evoco Bath Fill and Shower with HydroGlo™ Technology	Brushed Nickel	1.1967.008

### Features & Benefits

#### Temperature control

Thermostatic temperature stability

#### Easy to fit

Integrated push fit connections already included

Spanner free installation

Mira's innovative installation system, providing a simple first fix solution

Protective cover to minimise damage between first and 2nd fix

Flushing system provided to test connections prior to tiling

Suitable for rear wall and noggin installations

#### For your customer

Works on all systems, even at low pressure

Separate flow and temperature controls using button actuation

Maximum temperature stop for increased safety (with override for a hotter shower)

Choose your outlet - intuitive push button technology allows you to select the handset, bathfill or both

Mira Cool Shield™ to ensure valve doesn't get hot during showering

Mira Magni-flo™ technology delivers up to 3x more flow, even at low pressure

One spray 11cm multi-mode showerhead with rub-clean nozzles

1.25m flexible shower hose

The latest illuminating technology, no wiring or batteries required. Mira HydroGlo™ delivers extra experiences with no extra hassle.



# Product Specification

## Tech Details

### Temperature and flow control

Temperature control type: Thermostatic

Flow actuation: Push button

### Installation

Water entry points: Bottom only

Inlet connections: Direct 15mm push fit connections

Outlet connections: 15mm copper pipework

Reversed inlets supported: No = hot left, cold right only

### Supply Conditions (hot and cold)

Cold water range: 1°C to 25°C

Hot water range: Min 55°C; 60°C - 65°C (recommended)

Minimum maintained pressure (gas water heater) : 1 bar (10 metre head)

Minimum maintained pressure (gravity system) : 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

### Performance

Flow rate at 0.5 bar: 8.2 l/min (at Handset), 8.98 l/min (at Bath filler)

Flow regulator: 9 l/min (supplied with product - x2)

Temperature stability:  $\pm 2^{\circ}\text{C}$

### Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe max temp

Adjustable maximum temperature for on-site conditions

### Approvals

KIWA UK approved product

WRAS approved (Water Regulations Advisory Scheme)

TMV2 approved product

CE approved product

UKCA approved product



## Dimensions

